



# Vent Hood® WALL MOUNT LINER INSERT SPECIFICATIONS

**BHSLD LINER** Equipped with LED lighting. Not available with heat lamps.




**BHSLD**

## Connection Diagram (28 3/8" - 40 3/8" Widths)




**300 CFM B100 Single Blower (Top View)**

## Connection Diagram (28 3/8" - 46 3/8" Widths)




**600 CFM B200 Dual Blower (Top View)**


## Connection Diagram (46 3/8" Width)



**900 CFM B200 Dual & B100 Single Blower (Top View)**




**VP562 Transition (Optional) For B300 (B200 Dual Blower & B100 Single Blower)**



**VP562/VP563 transition centers outlet over top of hood**

## Recommended Mounting Height\*



\*Recommended mounting height is for optimum performance.

## Electrical/Mechanical Specifications For Blower Units

Model	Volts	Amps	Hz	RPM	CFM SP@0.0"	Equivalent CFM*	CFM SP@0.1"	CFM SP@0.2"	CFM SP@0.3"	Minimum Round Duct Size	Sones#
B100 Single	115	2.5	60	1550	300	450	273	245	225	6" (28 in. <sup>2</sup> )	5.4
B200 Dual	115	4.0	60	1550	600	900	531	480	430	8" (50 in. <sup>2</sup> )	6.5
B200 Dual & B100 Single	115	6.0	60	1550	900	1350	804	725	655	VP562: 10" (79 in. <sup>2</sup> )	6.3

Hood is available with LED lights (2 lights: 30" - 41", 3 lights: 42" - 48").

\* Because the Magic Lung® blower uses centrifugal filtration rather than conventional baffle or mesh filters, the Magic Lung® blower can handle cooking equipment with higher cubic feet per minute (CFM) requirements and can deliver equivalent CFM much more efficiently than other filtration systems. When comparing the Magic Lung® with other blower units made by other manufacturers, use the "Equivalent CFM".

# Ratings in accordance with the Standard Test Code by the Energy Systems Laboratory of the Texas Engineering Experiment Station.