



VentA Hood® WALL MOUNT RANGE HOOD SPECIFICATIONS


CWEH6-K Equipped with halogen lighting. Not available with heat lamps. Shown with optional duct cover (sold separately). Optional duct covers available in standard and custom sizes. Available in painted and stainless steel finishes. Available in 30", 36", 42", and 48" widths.




The VP521 transition is available for top vent applications at an additional charge.



Connection Diagram




(Top View)



(Front View)

Recommended Mounting Height*



*Recommended mounting height is for optimum performance.

Electrical/Mechanical Specifications For Blower Units

| Model | Volts | Amps* | Hz | RPM | CFM SP@0.0" | Equivalent CFM* | CFM SP@0.1" | CFM SP@0.2" | CFM SP@0.3" | Minimum Round Duct Size | Sones# |
|-----------------|-------|-------|----|------|-------------|-----------------|-------------|-------------|-------------|---------------------------|--------|
| K250 (Top Vent) | 115 | 2.2 | 60 | 1550 | 250 | 375 | 223 | 220 | 190 | 7" (38 in. ²) | 7.4 |

* Add 0.5 amp for each halogen light. Hood is available with halogen lights (2 lights: 30" & 36", 3 lights: 42" & 48").

Because the Magic Lung® blower uses centrifugal filtration rather than conventional baffle or mesh filters, the Magic Lung® blower can handle cooking equipment with higher cubic feet per minute (CFM) requirements and can deliver equivalent CFM much more efficiently than other filtration systems. When comparing the Magic Lung® with other blower units made by other manufacturers, use the "Equivalent CFM".

Ratings in accordance with the Standard Test Code by the Energy Systems Laboratory of the Texas Engineering Experiment Station.