



# VentA Hood® EUROSTYLE ISLAND RANGE HOOD SPECIFICATIONS


**EPIH18/SEPIH18** Equipped with halogen lighting. Not available with heat lamps. Shown with optional duct cover (sold separately). Optional duct covers available in standard and custom sizes.




**EPIH18**




**SEPIH18**




## Connection Diagram (36" - 48" Widths)




## Recommended Mounting Height\*



\*Recommended mounting height is for optimum performance.



**VP565 Standard Transition (Included)**



**Transition Installed (Side View)**

## Electrical/Mechanical Specifications For Blower Units

Model	Volts	Amps*	Hz	RPM	CFM SP@0.0"	Equivalent CFM*	CFM SP@0.1"	CFM SP@0.2"	CFM SP@0.3"	Minimum Round Duct Size	Sones#
T200 Island Dual	115	2.9	60	1550	550	900	507	471	431	8" (50 in. <sup>2</sup> )	6.0

\* Add 0.5 amp for each halogen light. Hood is available with halogen lights (one in each corner).

# Because the Magic Lung® blower uses centrifugal filtration rather than conventional baffle or mesh filters, the Magic Lung® blower can handle cooking equipment with higher cubic feet per minute (CFM) requirements and can deliver equivalent CFM much more efficiently than other filtration systems. When comparing the Magic Lung® with other blower units made by other manufacturers, use the "Equivalent CFM".

# Ratings in accordance with the Standard Test Code by the Energy Systems Laboratory of the Texas Engineering Experiment Station.

