





# Vent Hood® WALL MOUNT RANGE HOOD SPECIFICATIONS


**CWSH3** Equipped with halogen lighting. Not available with heat lamps. Available in 30", 36", and 42" widths. Shown with required blower/duct cover. Blower/duct covers available in standard sizes for 7' and 8' ceilings. Unit shipped as one assembly.



## Connection Diagram (30" - 42" Widths)





## Recommended Mounting Height



\*Recommended mounting height is for optimum performance.

## Connection Diagram (30" - 42" Widths)



## Electrical/Mechanical Specifications For Blower Units

Model	Volts	Amps*	Hz	RPM	CFM SP@0.0"	Equivalent CFM*	CFM SP@0.1"	CFM SP@0.2"	CFM SP@0.3"	Minimum Round Duct Size	Sones#
B100 Single	115	1.5	60	1550	300	450	273	245	225	6" (28 in. <sup>2</sup> )	5.4
B200 Dual	115	2.9	60	1550	600	900	531	480	430	8" (50 in. <sup>2</sup> )	6.5

\* Add 0.5 amp for each halogen light. Hood is available with halogen lights (2 lights: 30" - 41", 3 lights: 42" - 48", 4 lights: 54").  
 • Because the Magic Lung® blower uses centrifugal filtration rather than conventional baffle or mesh filters, the Magic Lung® blower can handle cooking equipment with higher cubic feet per minute (CFM) requirements and can deliver equivalent CFM much more efficiently than other than other filtration systems. When comparing the Magic Lung® with other blower units made by other manufacturers, use the "Equivalent CFM".  
 # Ratings in accordance with the Standard Test Code by the Energy Systems Laboratory of the Texas Engineering Experiment Station.